COPPER RETROFIT ROOF DRAINS



Pro Seal




"The Name Says It All!"


FEATURES

- Heavy Duty, Durable, Long Lasting Copper
- Also available in Spun Aluminum
- Strong Mechanical Seal Prevents Water Backups
- Large 3 Bolt Strainer Dome
- All Common Sizes Available
- Bolt Down Clamping Ring for Single-Ply Systems
- Variable Length Copper Outlets, Up to 15"

BEFORE COMPRESSION




AFTER COMPRESSION





SPECIFICATIONS



ADVANTAGES

- A Copper Drain with mechanical seal
- Also available in spun aluminum
- Compression of mechanical seal eliminates water backing up into roof system
- Fits all standard sizes of existing roof drains
- Installs from the rooftop using simple hand or power screwdriver with square head adapter
- Offered in variable length outlets, up to 15"
- Proven performance of both copper, aluminum drain and mechanical seal
- Economical to purchase and simple to install

INSTRUCTIONS





See website for installation instructions - www.marathondrains.com

ProSeal Installation Drivers: Drivers have special non-slip square heads to adapt to ProSeal expansion screws. Power shaft easily installs in any power drill for fast expansion of drain seal.

TYPE	SIZ	Œ	LENGTH
STRAIGHT (STR)	EXISTING DRAIN SIZE (A) inches/mm	OUTSIDE DIAMETER (B) inches/mm	STRAIGHT (C) inches/mm
ProSeal (STR) 3	3″ 76 mm	2.8" 72 mm	11″ 279 mm
ProSeal (STR) 4	4" 102 mm	3.78″ 96 mm	11″ 279 mm
ProSeal (STR) 5	5″ 127 mm	<i>4.70"</i> 119 mm	11″ 279 mm
ProSeal (STR) 6	6″ 152 mm	5.65" 144 mm	11″ 279 mm
Standard: ProSeal drains include 10" (203mm) high density polyethylene (black Plastic) strainer dome Options for ProSeal Drains: - CR clamping ring for straight styles only - drain outlets may be ordered extended by 6" (152 mm) - cast iron stainer dome - flange coatings: Asphalt, PVC or Plain (standard)			



Anality Products-for Professional Royfers